



# INDEPENDENT SLATE SUPPLIES

6 Gilston Road . Saltash . Cornwall . UK . PL12 6TW  
Tel: 01752 848080 Fax: 01752 848084  
EMAIL: info@independentslatesupplies.com

## ISS In-line vent range

- A perfect match every time
- Simple to install
- Economically priced
- Choice of grill colours





# INDEPENDENT SLATE SUPPLIES

6 Gilston Road . Saltash . Cornwall . UK . PL12 6TW


Tel: 01752 848080 Fax: 01752 848084

EMAIL: info@independentslatesupplies.com

## The ISS In-line vent range as roof space ventilator


### The ISS In-Line Slate Vent as roof space ventilator

The Slate Vent has a free air capacity of 10000mm<sup>2</sup>. One Slate Vent at 1.00 metre centres will achieve the equivalent of 10,000mm<sup>2</sup> per linear metre at low level. One Slate Vent at 2.00 metre centres will achieve the equivalent of 5,000mm<sup>2</sup> at high level.



### The ISS In-Line Slate Vent installed as soil vent or mechanical extract fan terminal

The Slate Vent can be adapted for connection to 110mm diameter pipe work. Adaptor and flexi-pipe are supplied separately.



The ISS In-Line available as:

**The ISS In-Line Smooth Vent 600 x 300mm and 500 x 250mm**

**The ISS In-Line Natural Vent.** A bespoke product whereby a natural slate acts as the upper cover with the catchment tray chemically bonded to it. A minimum width of 300mm applies allowing the following formats: 600 x 300mm, 500 x 300mm and 400 x 300mm. When used with slates of less than 300mm width, the adjacent slates require trimming along their length to maintain perps.



There is currently no British Standard test for driving rain testing. The Slate vent range has been tested at the Building Research Establishment for rain penetration. Test results and methods are available on request.

#### Exhausting air to atmosphere

Pressure Drop Across Vent (Pa)	Volume Flow Through Vent (litres/sec)
72	46.9
47	37.5
26	27.8
12	18.1
3	8.3
0	0